PMA 2123 BILIRUBIN PHOTOTHERAPY DETECTOR

SENSORS LABORATORY LIGHT MEASUREMENT

Delivery on all products is Stock to 2 weeks.

Every product is calibrated to NIST traceable standards before shipment.

1.6" (40.6 mm)

1.8" (45.8 mm)
Weight:
7.1 oz. (200 grams)

Height:



The PMA 2123 Bilirubin Phototherapy Detector is an accurate, stable detector designed to measure the output of phototherapy lamps used in neonatal wards to treat infant hyperbilirubenenima (jaundice). Blue light in the spectral range of 425-475 nm chemically alters bilirubin below the surface of the skin into products the infant can eliminate in urine.

The standard PMA2123 detector has a narrow spectral response from 425-475 nm, closely matching the action spectrum for bilirubin breakdown. The measurement will be accurate for the output of any lamp, in particular, blue fluorescent, daylight fluorescent and quartz halogen lamps commonly used in bili light units. The PMA2123 detector is calibrated to read in μ W/cm².

lises

The PMA2123 Bilirubin Phototherapy Detector is designed to measure the output of phototherapy lamps used in neonatal wards to treat infant hyperbilirubenenima (jaundice).

Alternate Views



Applications	Phototherapy Lamp monitoring High sensitivity Wide dynamic range	Determining length of exposure		Clinical studies	
Features		Excellent long term sta Cosine corrected	ability	NIST traceable calibration Selectable Units	
Specifications	Spectral response:				
	425-475 nm Range:		100		
	2,000 [μW/cm2] (Standard) ; 20,000 [μW/cm2] Display resolution:	(PMA2123C)	80		
	0.01 [μw/cm2]; 0.1[μW/m2] (PMA2123C) Operating environment:		Sensitivity (%)		
	32 to 120 °F (0 to +50 °C) no precipitation Cable:		8 40		
	5ft (1.5m) Diameter:		20 /		

PMA2123 Spectral Response

400

450

500

Wavelength (nm)

550

600

Solarmeter Australia - PO Box 1160, Noosaville DC, QLD, 4566. Ph: (07) 5474 9626 www.solarmeter.com.au - info@solarmeter.com.au